## **CLAIMS**

1. A system for data entry in a wireless communication device, the system comprising:

an audio-input device to receive audio-data;

- a voice-recognition engine to receive and analyze the audiodata, wherein the voice-recognition engine is configured to interpret the audiodata as matching a selected one of a set of alphanumeric characters to use in conjunction with the operation of the wireless communication device; and
- a memory to store the selected alphanumeric character for subsequent use in conjunction with the operation of the wireless communication device.
- 2. The system of claim 1 wherein the voice-recognition engine is further configured to interpret the audio-data as matching a selected one of a set of commands, the system further comprising a processor to execute the selected command.
- 3. The system of claim 1, further comprising a transmitter to transmit the selected alphanumeric character to a remote location.
- 4. The system of claim 1 wherein the memory stores a plurality of selected alphanumeric characters, the plurality of selected alphanumeric characters comprising at least a portion of an electronic message, the system further comprising a transmitter to transmit the electronic message to a remote location.
- 5. The system of claim 4 wherein the electronic message is compatible with a short-messaging-service protocol.

- 6. The system of claim 4 wherein the voice-recognition engine is further configured to interpret the audio-data as matching a selected one of a set of commands to process the electronic message, the system further comprising a processor to execute the selected command.
- 7. A system for storing addresses in a wireless communication device, the system comprising:

an audio-input device to receive audio-data;

- a voice-recognition engine to receive and analyze the audio-data, wherein the voice-recognition engine is configured to interpret the audio-data as matching a selected one of a set of alphanumeric characters;
- a processor to associate an address-identifier with a plurality of selected alphanumeric characters; and

a memory to store the plurality of selected alphanumeric characters in association with the associated address-identifier.

- 8. The system of claim 7 wherein the voice-recognition engine is further configured to interpret the audio-data as matching a selected one of a set of commands to process the plurality of selected alphanumeric characters and the associated address-identifier, the processor executing the selected command.
- 9. The system of claim 7 wherein the plurality of selected alphanumeric characters associated with the address-identifier represents at least part of a destination telephone number.
- 10. The system of claim 7 wherein the plurality of selected alphanumeric characters associated with the address-identifier represents at least part of an electronic address.

- 11. The system of claim 7 wherein the plurality of selected alphanumeric characters associated with the address-identifier represents at least part of a street address.
- 12. The system of claim 7 wherein the voice-recognition engine is further configured to interpret the audio-data as the address-identifier.
- 13. A method for data entry in a wireless communication device, the method comprising:

receiving audio-data;

configuring the wireless communication device to interpret the audio-data as matching a selected one of a set of alphanumeric characters to use in conjunction with the operation of the wireless communication device; and

storing the selected alphanumeric character for subsequent use in conjunction with the operation of the wireless communication device.

- 14. The method of claim 13, further comprising configuring the wireless communication device to interpret the audio-data as matching a selected one of a set of commands and executing the selected command.
- 15. The method of claim 13, further comprising transmitting the selected alphanumeric character to a remote location.
- of selected alphanumeric characters, the plurality of selected alphanumeric characters comprising at least a portion of an electronic message, and transmitting the electronic message to a remote location.
- 17. The method of claim 16 wherein the message is compatible with a short-messaging-service protocol.

- 18. The method of claim 16, further comprising configuring the wireless communications device to interpret the audio-data as matching a selected one of a set of commands to process the electronic message and executing the command.
- 19. A method for storing addresses in a wireless communication device, the method comprising:

receiving audio-data;

configuring the wireless communications device to interpret the audio-data as matching a selected one of a set of alphanumeric characters;

associating a plurality of selected alphanumeric characters with an address-identifier; and

storing the plurality of selected alphanumeric characters in association with the associated address-identifier.

- 20. The method of claim 19, further comprising configuring the wireless communication device to interpret the audio-data as matching a selected one of a set of commands to process the plurality of selected characters and the associated address-identifier and executing the selected command.
- 21. The method of claim 19 wherein the plurality of selected characters associated with the address-identifier represents at least part of a destination telephone number.
- 22. The method of claim 19 wherein the plurality of selected characters associated with the address-identifier represents at least part of an electronic address.
- 23. The method of claim 19 wherein the plurality of selected characters associated with the address-identifier represents at least part of a street address.

24. The method of claim 19, further comprising configuring the wireless communication device to interpret the audio-data as the address-identifier.